Galvanized Forklift Safety Access Cage 1 & 2 persons
LEDA-WP300-GALV

Product Overview

Z/LEDA/WP300/GALV

Load Capacity
300kg



Options

Safety harness with lanyard
Cage wheels

Delivery is calculated at checkout according to postcode and pallets used. Collection from our Kettering premises is free.

Specifications	
Length	1200 mm
Width	800 mm
O/A Height with Back Up (without wheels)	2000 mm
Height with Back Folded Down	1210 mm
Internal Height	1110 mm
Tool Tray Size	1000mm long x 140mm wide x 150mm deep
Fork Sleeves Dimensions	200mm wide x 100mm tall
Fork Sleeves Centres	800 mm, centre line to centre line
Weight	110 kg
Load Capacity	300 kg
Persons	Max 2 persons

Our WP300 Forklift Safety Access Cage (galvanized) is a very cost effective unit but yet a high quality is still maintained. The safety cage, also known as a forklift access platform, is safer than a ladder and less expensive and quicker than scaffolding and is manufactured in a rigid welded construction, not bolted together. It has a load capacity of 300kg and is suitable for 2 persons. The forklift cage has a galvanized finish. The deck of the cage is formed from 3mm steel chequer plate to provide grip for the operators to stand on. The back panel is covered with 50x50mm mesh to prevent any body parts from being caught in the forklift mast when being lifted. When not in use, the back panel folds down flat to save space. The door simply lifts up allows easy access in and automatically closes so no-one can fall out and is locked in place with a sprung loaded shoot bolt.