# Narrow Aisle 6 Step
## 1500mm

## Product Overview

**Z/STEP/6STEP/NARROWAISLE**

**Free Delivery**

**Load Capacity**
300kg



**Options**

Rubber Wheels
Galvanized
Basket

Mobile Steps lead time is generally 7-10 Days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then dispatch the ladders on a 3-day service.

| Specifications | |
|---|---|
| **Platform Height From Ground** | 1500mm |
| **Overall Width** | 540mm |
| **Length** | 1400mm |
| **Overall Height** | 2500mm |
| **Bottom Step Size** | 200mm x 460mm |
| **Platform Size** | 400mm x 400mm |
| **Step Tread Depth** | 200mm |
| **Step Tread Vertical Spacing** | 250mm |
| **Weight** | 62kg |
| **Load Capacity** | 300kg |

The narrow aisle mobile steps are based on our standard heavy duty range of steps — still with all the strength, but they don't have the wider rear axle. These narrow aisle steps have the wheels mounted under the framework of the steps. The steps are also fitted with an internal brake system as opposed to the side mounted lever to save space.

Our standard range sports 2 fixed castors at the rear end and 2 swivel castors at the front. These swivel castors can be raised so the steps frame bottoms out on the ground. The mobile ladder is fitted as standard with our industrial hi-grip steps, providing enhanced grip and stability, also a 100mm kick-plate and safety operating sticker.

Mobile steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized. The top platform width of the steps is always 400mm.