Easy Slope
1600mm

Product Overview

Z/STEP/EASY/1.6

Free Delivery

Step Width
550mm Standard
850mm Wide



Options

Rubber Wheels
RUGGED Wheels
Galvanized
Basket
Rear Safety Bar
Climb Prevention Bar
Bottom Gate
Swing out Rear Stabilisers
Front Levelling Legs
Access Platform
Access Platform Options
Forward Access
Right Access
Left Access
Left & Right Access

Mobile Steps lead time is generally 7-10 Days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then dispatch the ladders on a 3-day service.

Dimensions	Standard Step Width (550mm)	Wide Step Width (850mm)
Platform Height From Ground	1600mm	1600mm
Overall Length	1800mm	1800mm
Overall Height	2600mm	2600mm
Frame Width	600mm	900mm
Overall Axle Width	760mm	1060mm
Platform Size	550mm x 400mm	850mm x 400mm
Step Tread Width	550mm x 200mm	850mm x 200mm
Step Tread Vertical Spacing	200mm	200mm
Weight Standard Width	96kg	
Load Capacity	300kg	300kg

Most mobile steps used in warehouses have a slope of 60 degrees and a rise of 250mm, so you have to climb facing the treads and descend backwards. Our Easy Slope Range has a slope angle of 45 degrees and a comfortable step increment of 200mm, allowing users to descend facing forwards while carrying boxes. The downside is the increased overall length, which makes them a little less manoeuvrable.

These easy slope warehouse steps are made in one rigid structure giving good inherent strength. The 2 large rear wheels have a diameter of 200mm and at the front are 2 100mm wheels housed in swivel castors which are locked in place using a lever handle brake. The mobile ladder is fitted as standard with our industrial hi-grip steps, providing enhanced grip and stability, also a 100mm kick-plate and safety operating sticker.

Mobile steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized.